

# Rig Floor Computer (15' & 19")


## ATEX/IECEx Zone 2

*Innovative solutions for hazardous locations to drive efficiency.*



### SIMPLIFY

- ✓ Modern form factor for intuitive use.
- ✓ Integrate customer DAQ/decoder & software into a fully certified system.
- ✓ Reduce cabling with wireless interface to Safe-Area.
- ✓ Barriers are built-in.



### CONNECT

- ✓ Direct interface to dual pressure inputs.
- ✓ Standard connections for USB & LAN.
- ✓ Dual antenna ports for multi-band radio configuration.



### PERFORM

- ✓ Display & record all relevant drilling parameters with customer software.
- ✓ Reduce rig-up time.
- ✓ Operate from -40°C to +60°C



### *The Laversab Advantage*



#### OUTSTANDING SERVICE...

- ✓ Easily customizable solutions
- ✓ Simple setup and operation
- ✓ 24/7/365 Support



#### ...FOR A LIFETIME.

- ✓ 3-Year warranty (+2 years opt.)
- ✓ Rig-up & operation training
- ✓ High-performance CPU options

## Modernized design of Laversab's highly reliable Zone-2 computers

### Applications

- **Full function high performance Zone-2 Computer** for high reliability under extreme conditions
- **Customer-specific DAQ card or Decoder board can be integrated and Zone-2 certified**

### Common Uses

- Rig-Floor Computer
- Electronic Drilling Recorder
- MWD Surface System
- Vehicle-mounted Computer
- Driller's Display
- Remote Monitoring System

### Technical Specifications

|                            |  |                            |   |
|----------------------------|--|----------------------------|---|
| <b>Product Type</b>        | PC Workstation   | <b>Power</b>               | 90-260 VAC, 47-63 Hz, 150 VA  |
| <b>Certifications</b>      | ATEX / IECEx Zone-2  | <b>Operating Temp</b>      | −40°C to +60°C  |
| <b>Display &amp; Touch</b> | 15" & 19" XGA, with low-reflection capacitive touchscreen. Screen Resolution: 15" 1024 x 768<br>19" 1280 x 1024                | <b>Storage Temp</b>        | −40°C to +75°C  |
|                            |  | <b>Humidity</b>            | 5 to 100%   |
| <b>Brightness</b>          | 1000 nits; Sunlight readable with adjustable brightness  | <b>Sealing</b>             | IP66 on all six sides   |
| <b>Processor</b>           | Intel® Core™ Ultra 7 165H, 16Core, 24M Cache, 1.4GHz (5.0GHz) or Intel® Core™ Ultra 7 155U, 12Core, 12M Cache, 1.7GHz (4.8GHz) | <b>Weight</b>              | 2854: 16 lbs.<br>2864: 24 lbs.  |
|                            |  | <b>Dimensions</b>          | 2854: 14"(w), 11"(h), 3.3"(d)<br>2864: 16.75"(w), 13.75"(h), 3.89"(d) |
| <b>Operating System</b>    | Windows 10/11 Pro (or other)   | <b>Mounting</b>            | Hanger or Panel mount; VESA-100; Desktop stand                        |
| <b>Data storage</b>        | 512 GB to 2TB  |                            |   |
| <b>Memory</b>              | 16 to 96GB DDR5 RAM  | <b>Operating shock</b>     | 50 G, 11 ms half-sine   |
| <b>Wireless LAN</b>        | Wi-Fi radio (standard); 2.4GHz or 900MHz spread-spectrum   | <b>Operating vibration</b> | 3.0 G RMS, 5 to 500 Hz  |
| <b>External I/O</b>        | 2x USB3.1, 2x USB2.0 [Ex ic], 2x RS232 [Ex ic], 2x RS422/485 [Ex ic], 1x Gbit POE LAN (802.3af)                                |                            |   |