



Class 1 Division 1 Rig Floor Computer

Specifications on back

Model 2900 Class 1 Div 1 Rig Floor Computer

This Explosion-proof computer is fully sealed (NEMA-4) and can be operated in hazardous outdoor environments (including Class 1 Div 1), under severe vibration, and over a temperature range of -20°C to 50°C. It has an optional, intrinsically safe keyboard and mouse. The sunlight-readable 15" XGA display is clearly visible under all ambient light conditions and provides automatic brightness control. The small foot-print makes this the ideal computer for the Rig Floor.

Specifications

- CPU : Intel Atom Quad-core Processor @ 1.91 GHz
- Populated features: 8 GB DRAM; 128GB / 256GB SSD
- 15" sunlight-readable Ultra-Hibrite display, 1024 x 768 resolution, 1200 nits
- Auto-dimming feature for automatic brightness control
- Two USB ports, Barrier Protected, through sealed Cannon connector
- One Ethernet port, Barrier Protected, through sealed Cannon connector
- Optional, Intrinsically Safe Keyboard and Mouse
- LED indicator for "Heaters" status on front panel
- Mounting holes provided on the back of the unit.
- Windows 7 pre-loaded
- Operating power : 90-260 VAC, 50/60 Hz, 75 watts
- Internal Heater power : 90-260 VAC, 50/60 Hz, 150 VA
- Operating temperature : -20°C to 50°C
- Storage temperature : -40°C to 75°C
- Operating / Non-operating shock : 50 G, 11 ms half-sine
- Operating / Non-operating vibration : 3.0G RMS, 5 to 500 Hz
- Humidity : 5 to 100%
- Sealing : NEMA-4 on all six sides
- Weight : 39 lbs
- Dimensions : 16.0" (w) x 14.2" (h) x 4.2" (d)
- Certification : CSA C22.2 No. 30 , Explosion Proof, Class 1 Div 1 locations
Groups B, C & D ; Temp. code T6 at 50°C ambient



Houston, TX
Calgary, AB

Phone: (281) 325-8300
(403) 592-1720
Fax: (281) 525-8399
Website: www.laversab.com
E-mail: sales@laversab.com